

FlexWave™ WMX 300/305

WiMAX Subscriber Unit



ADC's FlexWave™ WMX 300 subscriber unit allows service providers to effectively serve the most demanding segment of the WiMAX user base: large businesses and enterprises. It delivers the entire range of functions required to suite virtually any business environment while supporting high speed service to hundreds of simultaneously connected users.

With the FlexWave WMX 300 performance meets intelligence—a single system can support hundreds of connected users of business and consumer applications: voice, web browsing, file downloads, streaming video, and other multi-megabit data services simultaneously managed over the wireless link.

The FlexWave WMX 300 supports the OFDM 256 FFT PHY and operates in licensed and licensed exempted WiMAX bands: 2.5 GHz, 3.5 GHz, and 5 GHz bands globally. FlexWave WMX 300 is compliant with the 802.16d-2004 standard and offers software upgradeability to the 802.16e-2005 amended standard in some models (WMX 305).

Features:

- IEEE 802.16d-2004 compliant
- Software upgradeable to 802.16e-2005 (some models)
- Enterprise grade performance and scale
- Service Level Agreement (SLA) Enforcement
- LOS, OLOS, NLOS deployments

SPEC SHEET



www.adc.com • +1-952-938-8080 • 1-800-366-3891



FlexWave™ WMX 300/305

WiMAX Subscriber Unit

The FlexWave WMX 300 delivers superior link performance, unsurpassed quality of service, and the broadest range of networking features for an optimized WiMAX deployment. Intuitive to provision, install and manage, the FlexWave WMX 300 is designed to help business subscribers reap the benefits of lower cost, multi-megabit wireless data service bypassing the complication and expense of leased wire line service.

The FlexWave WMX 300 is designed to meet a variety of subscribers and network requirements. The choice of capabilities includes: bridging, IP networking, integrated VoIP processing, extended range antennas, and a host of features allowing scalable differentiated services for the large business and enterprise customers.

Consisting of an outdoor radio with integral antenna, the FlexWave WMX 300 is interfaced to an indoor networking unit. An indoor unit interfaces to a standard Ethernet network and conveniently accepts AC power. Ethernet cabling carries network signaling and system power between the indoor and outdoor units. An optional external antenna is available for even greater gain.

Typical Applications

- High end customer premise equipment for large business and enterprise customers
- MDU/MTU access to hundreds of subscribers simultaneously
- Scalable differentiated services with application aware and subscriber aware traffic classification and prioritization
- Low cost multi-megabit data service alternative to expensive leased line service
- Emulated multi-T1/E1 circuits over WiMAX for interconnecting TDM traffic from PBXs, key systems and legacy TDM equipment
- Create “hot zones” by backhauling Wi-Fi access used for municipal and mesh network configurations
- Enterprise Voice over IP services

4/08 • 1 0 3 6 9 4 A E FlexWave™ WMX 300/305



FlexWave™ WMX 300/305

WiMAX Subscriber Unit

Specifications

RADIO AND SYSTEM SPECIFICATIONS

Compliance:

IEEE 802.16d-2004 (3.5T1, 3.5T2), ETSI HiperMAN, 802.16e-2005 upgradeable (some models)

Duplexing Mode, PHY:

TDD, OFDM, 256 FFT

Frequency:

3.3 – 3.4 GHz, 3.4 – 3.6 GHz, 5.725 – 5.925 GHz
Future: 2.5 – 2.7 GHz, 3.6 – 3.8 GHz 5.15 – 5.35 GHz, 5.425 – 5.725 GHz

Channel Bandwidth

WMX 300:

3.0 MHz, 3.5 MHz, 5.5 MHz, 7.0 MHz

WMX 305:

Future: 1.75 MHz, 5 MHz, 10 MHz

2.5 GHz (5.0 MHz, 10.0 MHz)

3.5 GHz (5.0 MHz, 7.0 MHz, 10.0 MHz)

Future: 1.75 MHz, 5 MHz, 10 MHz

Step Size:

250 KHz

Radio Output Power:

20 dBm; all frequencies

Receiver Sensitivity:

-95.1 dBm

Modulation:

BPSK, QPSK, 16QAM, 64QAM

Forward Error Correction:

Convolution coding 1/2, 2/3, 3/4

Integral Antenna Gain:

16 dBi @ 3.5 GHz

Optional External Antenna:

Yes

IP NETWORKING FEATURES/OPTIONS

IP Version:

IPv4 (RFC 791)

Bridging Mode:

IEEE 802.3d

VLANs:

IEEE 802.1 P/Q

SECURITY/ENCRYPTION

Authentication:

X.509 certificates

Encryption:

3DES, AES CCM 128, 1024

MULTI-SERVICE/MULTI-USER SUPPORT

Traffic Classifier:

MAC DA/SA, 802.1 P/Q, IP SA/DA IP Protection, IP TOS, TCP/UDP Port

Scheduling/QoS:

UGS, rtPS, nrtPS, BE, CIR, MIR

Active Connected Hosts:

250 max

Uni-directional Service Flows:

14 max

MANAGEMENT

Remote Management and Monitoring:

WaveCenter EMS Pro

Remote Management Access:

Telnet, SNMP, HTTP

Provisioning:

Centralized using WaveCenter EMS Pro

SNMP:

MIB II (RFC 1213), Enterprise MIB, IEEE 802.16f MIB

MECHANICAL

Outdoor Unit (HxWxD)/weight:

20.5 x 20.5 x 6.7 cm (8" x 8" x 2.6")/2.35 kg (5.2 lbs)
– including pole mount

Indoor Unit (HxWxD)/weight:

6 x 3.1 x 14.5 cm (1.2" x 2.3" x 5.7")/.45 kg (1 lb)

IDU-ODU Distance:

up to 100 m

ELECTRICAL

Input DC Voltage:

DC 36 – 57V (IEEE 802.3af compliant)

Max Input Current:

0.27A @ 48V DC

ENVIRONMENTAL

Weather Protection:

IP65/NEMA-4

Operating Temperature:

-35° to 60°C (-31° to 140°F)

Humidity (outdoor unit):

5 – 95% noncondensing

RoHS Compliant:

Yes

FlexWave™ WMX 300/305
4/08 • 103694AE

SPEC SHEET



Website: www.adc.com

From North America, Call Toll Free: 1-800-366-3891 • Outside of North America: +1-952-938-8080

Fax: +1-952-917-3237 • For a listing of ADC's global sales office locations, please refer to our website.

ADC Telecommunications, Inc., P.O. Box 1101, Minneapolis, Minnesota USA 55440-1101

Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ADC reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting our headquarters office in Minneapolis. ADC Telecommunications, Inc. views its patent portfolio as an important corporate asset and vigorously enforces its patents. Products or features contained herein may be covered by one or more U.S. or foreign patents. An Equal Opportunity Employer

103694AE 4/08 Revision © 2008, 2007 ADC Telecommunications, Inc. All Rights Reserved